



Slipway Trailer

SW 5-10

5

10

20

30

The Hydrotrans hydraulic boat trailer is designed to launch and recover boats on a slipway, transport the boats over land and park them in a storage or work area.

Slipway trailer

Unique handling Trailer to launch and recover boats on a slipway. Open U-frame design and V-shaped drawbar guarantee fast boat-handling, quick transport and easy parking. Independent lifting ensures that boats can be kept horizontal during transport and lifting. The ideal hull support consist of large, round and soft material. The moveable crossbeam guides the bow into the centre of the Slipway Trailer.

Hydrotrans

Lift & carry equipment

Windas 9
8441 RC Heerenveen
The Netherlands

Tel: +31 858 782 510
Fax: +31 848 833 774
Email: info@hydrotrans.nl

www.hydrotrans.nl





SW 5-10

Any pulling vehicle, such as an agricultural tractor, reach truck or fork lift truck, can be used to pull and push the Trailer. The hydraulic system of the “puller” is used to operate the hydraulic frame lifting functions of the Trailer. The Trailer is supplied with a tow-eye which can adjust in length direction of the puller. A manually operated control panel is part of the standard delivery.

Delivery

All Hydrotrans products are designed, manufactured and tested according to the European Conformity of Machines (CE) and are delivered with a comprehensive manual in English language. The standard warranty period is 1 year after delivery.

Technical specifications	SW 5	SW 10
Length	5750	7500
Width on hull support	1250	1500
Inside width	1000	1250
Overall width	1950	2200
Height on frame rear	550 - 1300 (min - max)	550 - 1300 (min - max)
Lifting height rear	750	750
Lifting capacity	5.000 kg	10.000 kg
Lifting	2 hydraulic cylinders with build in safety valves	
Wheels	2 pneumatic tires	4 pneumatic tires
Axles	2 axles with water-tight bearings	2 axles with water-tight bearings
Paint system	all steel parts are hot dip galvanized	
Boat length	3,50 M up to 9,50 M (min - max)	3,50M up to 13,50M (min - max)
Boat weight	500 up to 5.000 kg (min - max)	500 up to 10.000 kg (min - max)